

TIMER INSTALLATION MANUAL

IMEXPORT



1. THE TIMER MUST NOT BE USED AS AN ON/OFF SWITCH. THE EQUIPMENT MUST HAVE ITS OWN ON/OFF SWITCH OR CIRCUIT BREAKER.
2. CAREFULLY OBSERVE THE ELECTRICAL SPECIFICATIONS AND THE CORRECT HANDLING PROCEDURES FOR THE TIMER BEFORE INSTALLING IT IN THE EQUIPMENT.
3. THE TIMER MUST NEVER BE OPENED.
4. THE TIMER MUST NOT BE EXPOSED TO HUMID ENVIRONMENTS, IMMERSSED IN LIQUIDS, OR EXPOSED TO CORROSIVE OR OXIDIZING LIQUIDS OR VAPORS.
5. THE TIMER MUST NOT BE SUBJECTED TO IMPACTS OR DROPS.
6. THE ELECTRICAL TERMINALS OF THE TIMER MUST NEVER BE SOLDERED TO WIRING HARNESSSES OR WIRES.
7. THE ELECTRICAL TERMINALS MUST NOT BE DRILLED, AND ANY CHANGE TO THEIR ORIGINAL ANGLE MAY DAMAGE THE MECHANICAL ACTUATION SYSTEM.
8. THE TIMER SHAFT MUST NOT BE TURNED MANUALLY TOWARD THE "0" POSITION.

FOR ANY ADDITIONAL INFORMATION, PLEASE CONTACT US. WE WILL BE PLEASED TO ASSIST YOU.

EMAIL: IMEXPORT@IMEXPORT.COM.BR

IMEXPORT IND. COM. IMP E EXP. LTDA

Av. Júlio de Castilhos, 3898 | 95012-484 | Caxias do Sul | RS | Brazil

PHONE 0XX 54-3225-4122 | www.imexport.com.br